



- EPA Tier II exhaust emission compliant.
- Air-cooled, Single-cylinder, 4-stroke.
- All models feature direct injection.
- All models are counter balanced for high speed operation.
- Recoil & electric start options.
- Multiple PTO shafts available.

Electric start Add \$25.00 (with control box)

EPA Add \$40.00

Model	GE154	GE168	GE168-2	GE170	GE173	GE177	GE188	GE190
Engine Type	4-Stroke, Air-cooled, OHV Gasoline Engine							
Bore x Stroke (mm)	54x38	68x54	68x54	70x54	73x58	77x58	88x64	90x66
Displacement Capacity (cc)	87	163	196	209	242	270	389	420
Max. Output (Hp)/rpm	3.5/3600	5.5/3600	6.5/3600	7.0/3600	8.0/3600	9.0/3600	13.0/3600	16/3600
Max. Torque (N.m)			26/1250	26/1250	16.7/2500	19/2500	26.4/2500	26.5/2500
Fuel Consumption (g/hp.h)	255	260	270	265	260	260	260	272
Ignition System	Transistorized Magneto Ignition							
Spark Plug	E6TC	F6TC	F6TC	F6TC	F7TC	F7TC	F7TC	F7TC
Fuel Oil Tank Capacity (L)	1.6	3.1	3.1	3.6	6	6	6.5	6.5
Lubrication Oil	SAE 10W/30	SAE 10W/30	SAE 10W/30	SAE 10W/31	SAE 10W/32	SAE 10W/33	SAE 10W/35	SAE 10W/35
Lubrication Oil Volume (L)	0.4	0.6	0.6	0.6	1.1	1.1	1.1	1.1
Starting System	Recoil start	Recoil start	Recoil start	Recoil start	Recoil/Electric start			
Stop System	Ignition Primary Circuit Ground							
Noise Level at 7m (dB)	75	80	80	80	90	80	90	90
Gross Weight (kg)	11.5	17	18	18.5	26.5	27	33	33.5
DIM (L*M*H) (mm)	397x345x367	417x368x385	417x368x385	420x380x390	510x440x475	542x500x507	542x500x507	542x500x507
20'/40' FCL (pcs)	1200/594	1032/516	1032/516	938/444	539/258	384/176	384/176	384/176
FOB FUZHOU (USD)								

